

ULTRA-LOW-POWER ULTRASONIC WIND SENSOR (ULP STD)

Power: 3.3 - 18 VDC

Information Given:

- Wind Speed

Range: 0.5 - 45 m/s or 0 - 25 m/s (1.12 to 100 mph or 0 to 56 mph)

Accuracy: 0.1 m/s at 10 m/s (0.22 in. at 22 mph)

Threshold: 0.5 m/s (1.12 mph)

- Wind Direction:

Range: 0- 359°

Accuracy: $\pm 1^\circ$ RMS at 10 m/s (22.37 mph)

Measurement:

- Power Consumption

(UART) 0.15 mA at 38,400 bauds, 1 Hz (5V)

(RS485) 0.25 mA at 38400 bauds, 1 Hz (5V)

Baudrate: 2,400 to 115,200 (8n1) bauds

Output rate: 0.1 to 20 Hz (configurable)

Output units: m/s, Knots, or Km/h



Easy Mount

- 3xM4 lateral female tripod thread - UNC1/4"-20
- 3xM4 inferior female tripod thread - UNC1/4"-20

Sensor: Ultrasonic Transducers (4x)

Dimensions: Diameter: 70 mm (2.76 in.)
Height: 65 mm (2.55 in.)
Weight: 210grams (7.4 oz.)

Environmental:

- IP Protection IPX8

- Temperature Range

-15/60° C (5/140° F)

Firmware upgradable. Configurable via cable.

Data Output:

- RS485 / MODBUS	-Stream or Poll
- UART / 12C	-Stream or Poll
- 4-20mA	-Analog
- NMEA 2000	-Stream or Poll

